

 **ZINO®**



 **ZINO®** | **LED**
LIGHTING

Solution for a  **GREEN** planet

ENERGY EFFICIENT LIGHTS

LED

CONCEALED DOWNLIGHT

ZINO®



Jolly



Arc



Cornet



Sunny



Model No.	Concealed Model	Power	Housing	Cut out	Front	Height	Beam Angle
							All Size(in mm)
ZIN-500-10WJ	Jolly	10W	PC	80	110	60	120 degree
ZIN-500-8WA	Arc	8W	PC	70	107	45	120 degree
ZIN-500-7WC	Cornet	7W	PC	75	110	45	120 degree
ZIN-500-6WS	Sunny	6W	PC	75	110	25	120 degree

Features

- ZINO LED Chips mounted for soft lighting and equally distributed for higher CRI
- Anti-Glare and Frosted Diffuser for even light distribution
- Suitable for Concealed Box, False Ceiling, Wooden Cabinets
- All models are available in **AC as well as DC input volt**
- Available in **DOB as well as Driver Based option**
- Available in CW,WW,NW,R,G,B,P and 3 in 1 colour options



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED

CONCEALED DOWNLIGHT

ZINO®



Glare



Crystal


Crystal Big



Nexa Fibre



Edge



Model No.	Concealed Model	Power	Housing	Cut out	Front	Height	Beam Angle
ZIN-500-10WG	Glare	8W	PC	75	112	65	All Size(in mm) 120 degree
ZIN-500-9WC	Crystal	9W	Aluminium	70	112	43	120 degree
ZIN-500-15WCA	Crystal Big	15W	Aluminium	70	130	50	180 degree
ZIN-500-9WN	Nexa Fibre	9W	Aluminium	70	120	40	120 degree
ZIN-500-8WE	Edge	8W	PC	75	100	35	180 degree

Tech Specifications







Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

COB LENS

CONCEALED /
DEEP DOWNLIGHT

∴ ZINO®



					
Model No.	Model Name	Power	Cut size	Front size	Height
					All Size(in mm)
ZIN-50CP-4W	Lens Spot Deep	4W	55	75	42
ZIN-50CP-8W	Lens Spot Concealed	8W	80	105	47
ZIN-50CP3-8W	Lens Spot 3 in 1	8W	80	105	47
ZIN-50CP-12W	Lens Spot RECESS	12W	110	140	60

Features

- Modern elegant style of product with high brightness
- Adjustable Lens for Spot Focus
- Polycarbonate Housing with Metal Core Circuit and mounted ZINO LED
- Suitable for Concealed box(8W), Junction box(4W), False Ceiling/ Wooden Cabinet (12W)
- Available in all colour options CW, WW, NW, R, G, B and P
- 8W Lens COB also available in **3-in-1** colour option (CW-WW-NW, G-B-CW, R-B-P)









Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

ALINA COB - PC HOUSING (Concealed)

ZINO®



				
Model Number	Power	CutOut size	Outer size	Height
ZIN-50CA-6W	6W	74	108	68

All Size (in mm)

Technical Specifications

Beam Angle	> 60 degree
LED Lumens / Watt	> 120
Efficiency	> 85%
Material	PC
Input Range	85-300V AC 50HZ
Power Factor	>0.95 THD<20%
LED Colours	CW (6500K) NW (4000K) WW (3000K)
Housing Colour	White, Black
Reflector Colour	White, Gun Metal, Rose Gold, Copper
Usage	Indoor application including false ceiling, wooden cabinet etc.
Focus	Spot Focus



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED DEEP CRESCENT DOWNLIGHT

ZINO®



8W DEEP CRESCENT



15W DEEP CRESCENT




Model No.	Deep Model	Power	Housing	Cut size	Front size	Height	Beam Angle
-----------	------------	-------	---------	----------	------------	--------	------------

All Size(in mm)

ZIN-550-8WDC	Deep Crescent	8W	PC	40	88	45	180 degree
ZIN-550-15WDC	Deep Crescent	15W	PC	40	110	45	180 degree

Features

- Polycarbonate Housing with Metal Core Circuit and Mounted ZINO LED
- Anti-Glare and Frosted Diffuser for even light distribution
- Suitable for Junction Box(8W & 15W), Concealed Box(15W), False Ceiling etc.
- Available in CW, WW, NW, R, G, B, P and 3-in-1 colour option
- **15W Deep Crescent is suitable for both Concealed and Junction Box**



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED DEEP JUNCTION DOWNLIGHT

ZINO®



HEXA

NANO



DEEP SYRO



DEEP GLOW



DEEP SHINE



Model No.	Deep Model	Power	Housing	Cut size	Front size	Height	Beam Angle
ZIN-500-3WH	Deep Hexa	3W	PC	45	80	45	All Size(in mm) 120 degree
ZIN-500-3WA	Deep Nano	3W	PC	40	80	23	120 degree
ZIN-500-4WG	Deep Glow	4W	PC	45	80	35	120 degree
ZIN-500-8WS	Deep Syro	8W	PC	45	85	60	180 degree
ZIN-500-15WS	Deep Syro	15W	PC	45	135	60	180 degree
ZIN-500-8WD	Deep Shine	8W	PC	45	85	65	180 degree
ZIN-500-15WD	Deep Shine	15W	PC	45	140	65	180 degree

Features

- Polycarbonate Housing with Metal Core Circuit and mounted ZINO LED
- Anti-Glare and Frosted Diffuser for even light distribution
- Suitable for Junction Box, False Ceiling, Wooden Cabinets
- Available in CW, WW, NW, R, G, B, P and 3 in 1 colour option
- **8W Deep Shine available in AC as well as DC Input Volt**





Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

ADJUSTABLE FRAMELESS CONCEAL/DEEP PANEL

ZINO®



PUSH TO FIT SURFACE RINGS

COMPLETE PRODUCT

Model No. ⏴	Wattage Ⓜ	Shape ● ■	Category ⬠	Cutout Size (min) ↖ ↗	Cutout Size (max) ↖ ↗	Front Size ✧	Height ▮
ZIN-30F-12W ZIN-30F-20W	12W 20W	ROUND / SQUARE ROUND / SQUARE	SLIM SLIM	65 mm 65 mm	100 mm 150 mm	120 mm 170 mm	40 mm 40 mm
ZIN-30FS-12W ZIN-30FS-20W	12W 20W	ROUND / SQUARE ROUND / SQUARE	SLIM SLIM	— —	— —	120 mm 170 mm	43 mm 43 mm



12W CONCEALED ADJUSTABLE PANEL
(FLEXIBLE PCB)




12W DEEP ADJUSTABLE PANEL

Model No. ⏴	Wattage Ⓜ	Shape ● ■	Category ⬠	Cutout Size (min) ✧	Cutout Size (max) ✧	Front Size ✧	Height ▮
ZIN-30FF-12W ZIN-30FF-20W ZIN-30FD-20W	12W 20W 20W	ROUND / SQUARE ROUND / SQUARE ROUND / SQUARE	SLIM SLIM SLIM	65 mm 65 mm 45 mm	100 mm 150 mm 100 mm	120 mm 170 mm 120 mm	33 mm 33 mm 60 mm

Features

- High quality Polycarbonate diffuser with UV resistance
- Well managed heat emission, keep low temperature for better performance and longer lifetime
- Bright Diffused Light: Up to 80-percent light efficiency after diffuser
- Available in CW, WW, R, G, B, P and 3 in 1 colour option with switching / non switching mode








Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LUCENT COB - ALUMINIUM WITH PC FRONT


ZINO®



				
Model Number	Power	CutOut size	Outer size	Height
				All Size (in mm)
ZIN-50CL-5W	5W	62	72	40
ZIN-50CL-8W	8W	70	83	54
ZIN-50CL-12W	12W	90	105	63

Technical Specifications

Beam Angle	> 60 degree
LED Lumens / Watt	> 120
Efficiency	> 85%
Material	PC
Input Range	85-300V AC 50HZ
Power Factor	>0.95 THD<20%
LED Colours	CW (6500K) NW (4000K) WW (3000K)
Housing Colour	White, Black
Reflector Colour	White, Gun Metal, Rose Gold, Copper
Usage	Indoor application including false ceiling, wooden cabinet etc.
Focus	Adjustable / Tilttable spot focus



Tech Specifications









Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED DEEP DOWN LIGHTER/ PANEL

ZINO®



DEEP DOWNLIGHT

							
Model No.	Model	Power	Housing	Cut size	Front size	Height	Beam Angle
ZIN-30-12WDD	Deep Downlight	12W	PC	100	120	55	120 degree
ZIN-30-18WDD	Deep Downlight	18W	PC	130	150	60	120 degree

Features

- High quality Polycarbonate diffuser with UV resistance
- Well managed heat emission, keep low temperature for better performance and longer lifetime
- Bright Diffused Light: Up to 80-percent light efficiency after diffuser
- Slim construction for wider applications, durable and robust, anti-glare diffuser
- Available in all colour options - CW, WW, NW, R, G, B, P and 3 in 1 colour options



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

[

PROFILE Panel

]



Model No.	Wattage	Cut out size	Front size	Height
All Sizes (in mm)				
ZIN-30SP-15W	15W	150	170	30

Features

- High quality Polycarbonate housing with Innovative Design, for Recess Mounted Applications.
- Available in CW, WW, NW, R, G, B, P.




Tech Specifications






Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

2x2 Panel Astra Panel

ZINO®



2x2 Slim/Surface






				
Model No.	Power	Cut out size	Front size	Height
All Sizes (in mm)				
ZIN-22PS-40W	40W	596	596	40
ZIN-22PS-48W	48W	570	596	65
ZIN-22PS-80W	80W	570	596	65



Onboard Driver



External Driver

				
Model No.	Power	Cut out size	Front size	Height
All Sizes (in mm)				
ZIN-30AS-6W	6W	80	95	26
ZIN-30AS-12W	12W	105	130	26
ZIN-30ASN-12W	12W	105	130	40
ZIN-30AS-18W	18W	135	160	26

Features

- Well managed heat emission, keep low temperature for better performance and longer lifetime
- Bright Diffused Light: Up to 80-percent light efficiency after diffuser
- Slim construction for wider applications, durable and robust, anti-glare diffuser
- Available in all colour options - CW, WW, R, G, B, P



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

S Series Panel Slim+ Surface

ZINO®



Model No.	Wattage	Cut out size	Front size	Height
All Sizes (in mm)				
ZIN-30SS-8W	8W	100	115	35
ZIN-30SS-15W	15W	150	165	35
ZIN-30SS-20W	20W	200	220	35



Features

- High quality Polycarbonate housing with aluminium heat sink inside for proper heat dissipation.
- Recess Panel can be converted into Surface Panel with available external push to fit Surface Ring
- Available in CW, WW, NW, R, G, B, P and 3 in 1 colour options



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

Tango Slim Panel

Aluminium Slim Panel

ZINO®



Tango Slim Panel (PC)



Model No.	Wattage	Cut out size	Front size	Height
All Sizes (in mm)				
ZIN-30ST-10W	10W	100	129	22
ZIN-30ST-15W	15W	125	152	25
ZIN-30ST-20W	20W	200	178	25



Aluminium Slim Panel



Model No.	Power	Cut out size	Front size	Height
ZIN-30S-8W	8W	100mm	120mm	20mm
ZIN-30S-12W	12W	150mm	170mm	20mm
ZIN-30S-15W	15W	175mm	200mm	20mm
ZIN-30S-18W	18W	205mm	225mm	20mm

Features

- **TANGO PANEL**-High quality low height slim panel in PC housing.
- **ALUMINIUM SLIM PANEL**-Powder coated aluminium housing for better heat dissipation with Flexible PCB inside.
- Modern & Elegant appearance makes the ceiling more graceful.
- Available in CW, WW, NW, R, G, B, P colour options.



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

Surface Panels

Polycarbonate -
Full Diffuser

ZINO®



Twister - Surface



Surface Glory



Model No.

Model Name

Power

Dia

Height

All Size(in mm)

ZIN-400PT-8W

Surface - Twister

8W

90

50

ZIN-400PT- 12W

Surface - Twister

12W

120

50

ZIN-400PT3-12W

Surface - Twister 3 in 1

12W

120

50

ZIN-400P-8W

Surface - Glory

8W

85

44

ZIN-400P-15W

Surface - Glory

15W

140

44

Features

- LED Surface Panel in Polycarbonate Housing
- Innovated design for surface mounted applications.
- High Grade Aluminium Heat Sink for better heat dissipation
- Available in CW, WW, NW, R,G,B,P colour options




Tech Specifications


Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

D-SERIES SURFACE PANELS






ZINO®



ROUND TRIM SURFACE PANEL



SQUARE TRIM SURFACE PANEL

				
Model No.	Model Name	Power	Dia	Height
ZIN-400DS-6W	TRIM SURFACE PANEL	6W	90	28
ZIN-400DS-12W	TRIM SURFACE PANEL	12W	120	28
ZIN-400DS-18W	TRIM SURFACE PANEL	18W	155	28

All Size(in mm)

Features

- LED Surface Panel in Polycarbonate Housing
- Innovated sleek design for surface mounted applications.
- High Grade Aluminium Heat Sink for better heat dissipation
- Available in CW, WW, NW, R,G,B,P colour options



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

SURFACE PANELS

ZINO®



ALUMINIUM SURFACE PANEL



TRIM SURFACE PANEL PC



Model No.	Surface Model	Power	Dia	Height
All Size(In mm)				
ZIN-400-8W	Surface Metal	8W	120	35
ZIN-400-12W	Surface Metal	12W	170	35
ZIN-400-15W	Surface Metal	15W	170	35
ZIN-400-18W	Surface Metal	18W	220	35
ZIN-400P-12W	Surface PC	12W	120	30
ZIN-400P-18W	Surface PC	18W	150	30

Features

- LED Surface Panel with Powder Coated Aluminium Housing
- High Grade Aluminium Heat Sink for better heat dissipation
- Available in CW, WW, NW, R,G,B,P colour options



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

COB Spot Button / Striker

ZINO®



2W BUTTON



3W LENS STRIKER PC

 Model No.	 Model Name	 Housing
ZIN-500-2BL ZIN-500-3LS	2W SPOT BUTTON 3W LENS STRIKER	PC PC

Features

- Spot highlighter in wooden cabinet, Mirror, False Ceiling etc.
- External as well as Inbuilt onboard driver facility
- Available in CW, WW, NW, R, G, B and P



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

COB LIGHTS (ALUMINIUM)

ZINO®



ADJUSTABLE COB

DEEP COB



Model Number	Model Name	Power	Cutout Size	Outer Size	Height
					All Size(in mm)
ZIN-50C-9W	Adjustable COB	9W	75	88	75
ZIN-50C-16W	Adjustable COB	16W	100	113	80
ZIN-50C-30W	Adjustable COB	30W	140	157	115
ZIN-50C-50W	Adjustable COB	50W	140	157	130
ZIN-50CD-12W	Deep COB	12W	55	80	75
ZIN-50CD-18W	Deep COB	18W	60	90	90

Technical Specifications

Beam Angle	> 60 degree
LED Lumens / Watt	> 130-140
Efficiency	> 85%
Material	Pressure Die Cast Aluminium with soft diffuser
Input Range	85-300V AC 47-60HZ
Power Factor	>0.95 THD<20%
LED Colours	CW (6500K) NW (4000K) WW (3000K)
Housing Colour	White
Usage	Indoor application including false ceiling, Wooden cabinet etc.



Tech Specifications



Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

COB Track / WALL SPOT LIGHT

ZINO®





TRACK LIGHT / WALL SPOT

 Model Number	 Power
ZIN-50CT-9W	9W
ZIN-50CT-16W	16W
ZIN-50CT-30W	30W
ZIN-50CT-50W	50W
ZIN-50IT-10W	10W
ZIN-50IT-20W	20W
ZIN-50IT-30W	30W



TRACK CHANNEL

 Model Number	 Length
ZIN-50CTB-1	1 mtr
ZIN-50CTB-2	2 mtrs
ZIN-50CTW-1	1 mtr
ZIN-50CTW-2	2 mtrs

Technical Specifications

Watt	6W, 9W, 16W, 30W, 50W
Beam Angle	>60 degree
LED Lumens/ Watt	>130-140
Efficiency	>85%
Material	Pressure Die Cast Aluminium
Input Range	85-300V AC 47-60HZ
Power Factor	>0.95
LED Colours	CW (6500K) NW (4000K) WW (3000K)
Housing Colours	White Black
Track Channel Colours	White Black
Usage	Indoor Applications
Focus	Adjustable in all directions, movable facility in track channel.



Tech Specifications


Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED BULKHEAD LIGHT

ZINO®



10W BULKHEAD



20W BULKHEAD 3-IN-1



20W BULKHEAD CUM STREETLIGHT FROSTED DIFFUSER



12W BULKHEAD ALUMINIUM HOUSING



Model No.

Power

Size (L*W*H)

ZIN-BL-10W

10W

170*70*50mm

ZIN-BL-20W

20W

210*100*55mm

ZIN-BLC-20W

20W

165*82*68mm

ZIN-BLA-12W

12W

200*107*55mm

Features

- Robust lighting style for outside areas and large indoor spaces
- Designed tough enough to withstand dust, water and high/low temperature
- Innovative design with Surface Mounted Applications
- Available in **DOB** as well as **Driver Based** option
- Available in CW,WW,R,G,B,P and 3 in 1 colour option
- 10W BULKHEAD available in both **AC and DC input mode**



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

FLOOD LIGHT LENS MODEL

ZINO®



Model No.

Power

Frame Size (L*W*H) mm

Housing

ZIN-50FPSL-20W

20W

140*130*25

PC

ZIN-50FLL-30W

30W

185*185*40

ALUMINIUM

ZIN-50FLL-50W

50W

215*205*405

ALUMINIUM

ZIN-50FLL-100W

100W

284*280*40

ALUMINIUM

ZIN-50FLL-150W

150W

310*300*45

ALUMINIUM

ZIN-50FLL-200W

200W

310*300*45

ALUMINIUM

ZIN-50FLL-400W

400W

415*370*80

ALUMINIUM

Features

- Robust lighting style for outside areas and large indoor spaces
- Designed tough enough to withstand dust, water and high/low temperature
- Innovative design with Surface Mounted Applications
- Available in CW, WW, NW, R, G, B and P




Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 6 KVA

FLOOD LIGHT DIAMOND REFLECTOR

ZINO®



Model No.

Power

Frame Size (L*W*H) mm

ZIN-50FDL-50W	50W	215*205*60
ZIN-50FDL-70W	70W	215*205*60
ZIN-50FDL-100W	100W	276*245*70
ZIN-50FDL-150W	150W	305*285*70
ZIN-50FDL-200W	200W	345*325*80
ZIN-50FDL-250W	250W	345*325*80
ZIN-50FDL-300W	300W	415*370*80
ZIN-50FDL-350W	350W	415*370*80
ZIN-50FDL-400W	400W	415*370*80
ZIN-50FDL-500W	500W	500*340*80
ZIN-50FDL-600W	600W	600*400*170
ZIN-50FDL-1000W	1000W	600*400*170

Features

- Robust lighting style for outside areas and large indoor spaces
- Designed tough enough to withstand dust, water and high/low temperature
- Innovative design with Surface Mounted Applications
- Available in CW, WW, NW, R, G, B and P



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 6 KVA

Street Light Lens Model

ZINO®







Lens Street Light



Slim Lens Street Light



PC Street Light

			
Model No.	Wattage	Frame Size (L*W*H)	Housing
ZIN-50STP-20W	20W	310*100*50mm	PC
ZIN-50STL-24W	24W	290*105*50mm	ALUMINIUM
ZIN-50STL-30W	30W	345*125*50mm	ALUMINIUM
ZIN-50STL-36W	36W	345*125*50mm	ALUMINIUM
ZIN-50STL-50W	50W	380*160*55mm	ALUMINIUM
ZIN-50STL-60W	60W	380*165*55mm	ALUMINIUM
ZIN-50STL-100W	100W	525*180*60mm	ALUMINIUM
ZIN-50STL-200W	200W	450*230*70mm	ALUMINIUM
ZIN-50STS-30W	30W	355*50*60mm	ALUMINIUM
ZIN-50HTLS-50W	50W	380*50*60mm	ALUMINIUM

Features :

"Aluminium housing with moulded silicon gasket"

PG7 PP Gland & SS Bolts & Screws



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 6 KVA

Highbay Lens Model

ZINO®



50W



100W



150W-200W




250W-300W



Model No.	Power	Dia (mm)	Height(mm)
ZIN-70HBL-50W	50W	185	50
ZIN-70HBL-100W	100W	230	60
ZIN-70HBL-150W	150W	320	70
ZIN-70HBL-200W	200W	320	70
ZIN-70HBL-250W	250W	370	85
ZIN-70HBL-300W	300W	370	85

Features

- Mounted via a pendant or chain, or directly to a ceiling or ceiling girder
- Used where height is more than 20ft and upto 80 ft from ground level
- Covers vast vertical and horizontal space
- Available in High Power LED and 1W 2835 LED Option
- Available in all colour options - CW, WW,R,G,B,P



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 6 KVA

Gate Light

ZINO®



12W CRYSTAL



12W FOUNTAIN



20W MOON

15W GATE LIGHTS



ULTMA



LOTUS



RAINBOW



AVIVA



PERISH



TOSHIBA



ZIKZAK



PUMA



CAPTAN



GLIDER




JUGNU



ELECTRA



STAND



Features

Available in both full powder coated aluminium housing as well as Polycarbonate housing

Exclusive designed different categories of PC glass for elegant lighting reflection and output

Available in both mounted LED's in MCPCB as well as LED bulb option in B22 and E27 cap

Available in all colour options - CW, WW, R, G, B, P




Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED BULB LED STRIPS

ZINO®



MODEL No. 	Model Name 	Size(H*W) mm 
ZIN-100-5W	5W LED Bulb	111*57
ZIN-100-7W	7W LED Bulb	111*57
ZIN-100-9W	9W LED Bulb	111*57
ZIN-100-15W	15W LED Bulb	130*70
ZIN-100-20W	20W LED Bulb	135*80
ZIN-100-40W	40W LED Bulb	190*120
ZIN-100-50W	50W LED Bulb	220*140
ZIN-100D-9W	9W LED DC Bulb	100*55



LED STRIPS AND ADAPTOR

LED TYPE	2835, 5050
LED COUNT(Per metre)	60, 120, 240, 480 LED'S
COLOUR OPTION	CW, WW, NW, R, G, P, B

ADAPTOR- 1amp, 2.5amp, 3amp, 5amp, 10amp

FEATURES

- Powered coated aluminium housing with glossy diffuser
- Quick reaction, no flash, reaching to full luminous output immediately after turn on
- B22** and **E27** cap available
- DOB** as well as **DRIVER BASED** option available
- Available in **AC** and **DC** input mode (5W,7W,9W)
- Available in colour options : CW,WW,NW,R,G,B,P



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

WALL WASHER SPIKE LIGHT

ZINO®



WALL WASHER

Power	Housing	Frame Size (L*W*H)mm
50W	Aluminium	510x55x80
100W	Aluminium	285x72x72



GARDEN SPIKE LIGHT

Power	Housing	Height
5W	Aluminium	60mm
9W	Aluminium	65mm
12W	Aluminium	160mm

Features

- High quality aluminium Die-cast moulding
- Anti UV electrostatic powder coating SS fasteners
- High strength and strong corrosion resistance
- Available in CW, WW,P, R, G, B, RGB



Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

LED/COB WALL LIGHT

ZINO®



C SERIES 1+1



C SERIES 2+2



C SERIES 3+3



4 Way



2 Way Slim




1 Way Slim



HALF K



FULL K




Foot Light



SURFACE CYLINDER



HANGING CYLINDER



STEP LIGHT

Model No.	Model Name	Power
ZIN-601-4W	C-SERIES 1+1 Wall Light	4W
ZIN-601-8W	C-SERIES 2+2 Wall Light	8W
ZIN-601-12W	C-SERIES 3+3 Wall Light	12W
ZIN-602-5W	Half K Wall Light	5W
ZIN-602-10W	Full K Wall Light - K Shape	10W
ZIN-603-3W	Foot Light	3W
ZIN-604-3W	Step Light	3W
ZIN-604-5W	Step Light	5W

Model No.	Model Name	Power
ZIN-605-4W	2 Way Slim Wall Light	4W
ZIN-605-2W	1 Way Slim Wall Light	2W
ZIN-606-8W	4 Way Wall Light (Single Colour)	8W
ZIN-606-4W	4 Way Wall Light (R,G,B,P)	4W
ZIN-607-6W	Surface/Hanging Cylinder Black/White	6W
ZIN-607-12W	Surface/Hanging Cylinder Black/White	12W
ZIN-607-18W	Surface/Hanging Cylinder Black/White	18W

Tech Specifications

Input Voltage - 120-300V AC | IP-20 | Inbuilt Driver | CRI > 80 | PF>0.9 | Surge Protection - 4 KVA

COMPANY PROFILE

Zino Electronics Pvt. Ltd. was established in 2020. Company has complete business solutions for LED Lights under single window.

Company have in-house PCB designing, PCB Manufacturing, SMT Lines, LED Lights driver designing & manufacturing facility, R&D team, testing lines and complete product assembling.

Company has constantly worked towards quality enhancing, product & technology updation and has been delivering customized solutions as per the customer needs.

Company is serving in Entire Indian market with more than 80% business from repeated and satisfied customers.

MISSION AND VISION

The company's mission is to inspire brand loyalty in customers, it works with a vision to assume the distinction of global leader through affordable manufacturing services & solutions.



ZINO ELECTRONICS PVT. LTD.

CORPORATE ADDRESS

Sec.6, Park Vasundhra, Ghaziabad, Uttar Pradesh-201012

Web : www.zinoelectronics.in

Contact No. : +91-7696901800

Customer care: zinoelectronicsofficial@gmail.com

